

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re Application of: Robert G. Arsenault, et al.

Date: March 22, 2006

09/677,691

Group Art Unit: 2617

Filed: October 2, 2000

For: METHOD AND APPARATUS FOR PROVIDING NON-  
RESIDENT PROGRAM GUIDE INFORMATION TO A  
MEDIA SUBSCRIBER

Examiner: Anna Q. Shang

**APPEAL BRIEF  
TRANSMITTAL LETTER**Mail Stop Appeal Briefs – Patents  
Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

Sir:

Enclosed is the Appeal Brief for the above-identified patent application.

\_\_\_\_\_ Applicant petitions for an extension of time for \_\_\_\_\_ months(s). If an additional extension of time is required, please consider this a petition therefor.


_____ An extension for _____ months(s) has already been secured; the fee paid therefor of	Fee \$ _____
is deducted from the total fee due for the total months of extension now requested.	\$ _____
Extension fee due with this request	\$ _____

X Applicant believes that no extension of time is required. However, this conditional petition is being made to provide for the possibility that applicant has inadvertently overlooked the need for a petition for extension of time.

X The Appeal Brief Fee of \$ 500.00 is due.

X The total fee due is \$500.00. Please charge this amount to Deposit Account No. 50-0383 of The DIRECTV Group, Inc. (formally Hughes Electronics Corporation), El Segundo, California. If any additional appeal brief fee or extension fee is required, please charge to Deposit Account No. 50-0383.

Respectfully submitted,

  
 Georgann S. Grunebach, Registration No.: 33,179  
 Attorney for Appellants
**CERTIFICATE OF MAILING UNDER 37 CFR 1.8**

I hereby certify that this correspondence is being filed with the United States Postal Service with sufficient postage as FIRST CLASS MAIL, and is addressed to Mail Stop Appeal Brief – Patents, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on March 22, 2006, by Georgann S. Grunebach, Registration No. 33,179.

(Date of 1<sup>st</sup> Class Mailing)

(Person certifying mailing of correspondence)

 The DIRECTV Group, Inc.  
 Patent Docket Administration  
 Bldg. R08, M/S A109  
 PO Box 956  
 El Segundo, CA 90245-0956  
 Telephone: (310) 964-4615  
 Date: **March 22, 2006**
  
 (Signature of person certifying mailing)

March 22, 2006  
 (Date of Signature)



Due Date: March 27, 2006

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**  
**BEFORE THE BOARD OF PATENT APPEALS AND INTERFERENCES**

In re Application of:

Inventor: Robert G. Arsenault et al.

Serial No.: 09/677,691

Filed: October 2, 2000

Title: METHOD AND APPARATUS FOR  
PROVIDING NON-RESIDENT PROGRAM  
GUIDE INFORMATION TO A MEDIA  
SUBSCRIBER

Examiner: Annan Q. Shang

Group Art Unit: 2617

Appeal No.: \_\_\_\_\_

**BRIEF OF APPELLANTS**

MAIL STOP APPEAL BRIEF - PATENTS

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

Dear Sir:

In accordance with 37 CFR §1.192, Appellants hereby submit the Appellants' Brief on Appeal from the final rejection in the above-identified application, as set forth in the Office Action dated November 28, 2005.

Please charge the amount of \$500 to cover the required fee for filing this Appeal Brief as set forth under 37 CFR §1.17(c) to Deposit Account No. 50-0383. Also, please charge any additional fees or credit any overpayments to Deposit Account No. 50-0383.

03/27/2006 YPOLITE1 00000091 500383 09677691

01 FC:1402 500.00 DA

## I. REAL PARTY IN INTEREST

The real party in interest is THE DIRECTV GROUP, INC. the assignee of the present application.

## II. RELATED APPEALS AND INTERFERENCES

There are no related appeals or interferences for the above-referenced patent application.

## III. STATUS OF CLAIMS

Claims 1-7, 9-15, 17-23, 25-31, 33-39, 41-47 and 49 are pending in the application.

Claims 1-7, 9-15, 17-23, 25-31, 33-39, 41-47 and 49 were rejected under 35 U.S.C. §102(e) as being obvious in view of U.S. Patent No. 6,401,242 to Eyer (hereinafter "Eyer"), and these rejections are being appealed.

## IV. STATUS OF AMENDMENTS

No amendments to the claims have been made subsequent to the final Office Action.

## V. SUMMARY OF CLAIMED SUBJECT MATTER

The Applicants' invention is a system and method that provides program guide information to subscribers. In one embodiment, the method is applied to a satellite broadcasting system (600), as illustrated in FIG. 2 (reproduced below). The satellite broadcasting system (600) has a first satellite (602) broadcasting a first signal (650) having a first set of program material and first program guide information describing at least a portion of said set of program material, and a second satellite (604) broadcasting a second signal (652) having a second set of program material and second program guide information describing at least a portion of said second set of program material, wherein the first signal (650) and the second signal (652) each include service channels uniquely described by a service channel identifier.




FIG. 6

In the broadcast system described above, one embodiment of the method comprises the steps of mapping at least a portion of the first program guide information to a first service channel of the first broadcast signal (block 902 of FIGs. 9A and 9B and page 24, lines 19-24), mapping at least a portion of the second program guide information to a second service channel of the first signal (block 904 of FIGs. 9A and 9B and page 24, lines 24-26), wherein the second service channel is logically offset from the first service channel (page 24, lines 26-30), and transmitting the first signal to the subscriber (page 23, lines 4-5 and block 906 of FIGs. 9A and 9B), wherein the second program guide information includes data identifying the service network transmitting the second program guide information (block 1002 of FIGs. 10A and 10B and page 27 lines 3-7) and wherein the first program guide information and the second program guide information is merged according to a comparison between the data and a receiver station configuration value (FIG. 10B and page 27, line 15- page 29, line 3).

In an analogous broadcasting system described above, another embodiment of the method comprises the steps of receiving the first signal (FIG. 10B, page 27, lines 15-17), and presenting the first program guide information and the second program guide information to a subscriber (block 1034 of FIG 10C, page 32, lines 1-4). The first signal includes a first service channel having at least a portion of the first program guide information (FIGs. 9A and 9B and page 24, lines 19-24); a

second service channel having at least a portion of the second program guide information signal (block 904 of FIGs. 9A and 9B and page 24, lines 24-26); and the second service channel is logically offset from the first service channel (page 24, lines 26-30). Further, the second program guide information includes data identifying the service network transmitting the second program guide information (block 1002 of FIGs. 10A and 10B and page 27 lines 3-7) and the first program guide information and the second program guide information is merged according to a comparison between the data and a receiver station configuration value (FIG. 10B and page 27, line 15- page 29, line 3).

In an analogous broadcasting system described above, another embodiment of the invention is evidenced by an apparatus for providing at least a portion of the second program guide information to a receiver station receiving the first signal. The apparatus comprises a program guide subsystem (item 206 in FIG. 2, further disclosed in FIG. 3 and discussed in page 8, line 14 - page 10, line 2 of the specification) for mapping at least a portion of the first program guide information to a first service channel of the first broadcast signal, and mapping at least a portion of the second program guide information to a second service channel of the first broadcast signal, wherein the second service channel is logically offset from the first service channel (disclosed in the specification as described above); and a transmitter (block 222 of FIG. 2, discussed at page 10, line 17) for transmitting the first signal to the receiver station (block 110 of FIG. 1 and page 6, line 9 of the specification); wherein the second program guide information includes data identifying the service network transmitting the second program guide information and wherein the first program guide information and the second program guide information is merged according to a comparison between the data and a receiver station configuration value (see block 1002 of FIGs. 10A and 10B and page 27 lines 3-7; and FIG. 10B and page 27, line 15- page 29, line 3).

In an analogous broadcasting system described above, another embodiment of the invention is evidenced by an apparatus for obtaining at least a portion of the second program guide information via the first signal. The apparatus comprises a tuner (block 504 of FIG. 5 and page 11, line 8) for receiving the first signal (FIG. 10B, page 27, lines 15-17), and a presentation device (page 26, lines 5-6) for presenting the first program guide information and the second program guide information to a subscriber (block 1034 of FIG 10C, page 32, lines 1-4). The first signal includes a

first service channel having at least a portion of the first program guide information (FIGs. 9A and 9B and page 24, lines 19-24); a second service channel having at least a portion of the second program guide information signal (block 904 of FIGs. 9A and 9B and page 24, lines 24-26); and the second service channel is logically offset from the first service channel (page 24, lines 26-30). Further, the second program guide information includes data identifying the service network transmitting the second program guide information (block 1002 of FIGs. 10A and 10B and page 27 lines 3-7) and the first program guide information and the second program guide information is merged according to a comparison between the data and a receiver station configuration value (FIG. 10B and page 27, line 15- page 29, line 3).

In an analogous broadcasting system described above, embodiments of the invention are also described by the structures, materials, or acts corresponding to the following:

Claim(s)	Structure(s), material(s), or act(s) corresponding to:	Found At
33	means for mapping at least a portion of the first program guide information to a first service channel of the first broadcast signal	(item 206 in FIG. 2, further disclosed in FIG. 3 and discussed in page 8, line 14 - page 10, line 2 of the specification)
33	means for mapping at least a portion of the second program guide information to a second service channel of the first broadcast signal, wherein the second service channel is logically offset from the first service channel	(item 206 in FIG. 2, further disclosed in FIG. 3 and discussed in page 8, line 14 - page 10, line 2 of the specification)
33	means for mapping at least a portion of the second program guide information to a second service channel of the first broadcast signal, wherein the second service channel is logically offset from the first service channel	(item 206 in FIG. 2, further disclosed in FIG. 3 and discussed in page 8, line 14 - page 10, line 2 of the specification)
41	means for receiving the first signal, wherein the first signal includes:	(block 504 of FIG. 5 and page 11, line 8)

Claim(s)	Structure(s), material(s), or act(s) corresponding to:	Found At
41	means for mapping at least a portion of the second program guide information to a second service channel of the first broadcast signal, wherein the second service channel is logically offset from the first service channel	(item 206 in FIG. 2, further disclosed in FIG. 3 and discussed in page 8, line 14 - page 10, line 2 of the specification)

In an analogous broadcasting system described above, embodiments of the invention are also described by a signal embodied in a carrier wave, the signal produced by performing the method steps of mapping at least a portion of the first program guide information to a first service channel of the first broadcast signal (block 902 of FIGs. 9A and 9B and page 24, lines 19-24), mapping at least a portion of the second program guide information to a second service channel of the first signal (block 904 of FIGs. 9A and 9B and page 24, lines 24-26), wherein the second service channel is logically offset from the first service channel (page 24, lines 26-30), and transmitting the first signal (page 23, lines 4-5 and block 906 of FIGs. 9A and 9B), wherein the second program guide information includes data identifying the service network transmitting the second program guide information (block 1002 of FIGs. 10A and 10B and page 27 lines 3-7) and wherein the first program guide information and the second program guide information is merged according to a comparison between the data and a receiver station configuration value (FIG. 10B and page 27, line 15- page 29, line 3).

#### VI. GROUNDS OF REJECTION TO BE REVIEWED ON APPEAL

Whether claims 1-7, 9-15, 17-23, 25-31, 33-39, 41-47 and 49 are patentable under 35 U.S.C. § 102(e) over Eyer.

## VII. ARGUMENT

### A. The References

#### 1. *The Eyer Reference*

U.S. Patent No. 6,401,242, issued June 4, 2002 to Eyer et al. discloses a method and apparatus for designating a preferred source to avoid duplicative programming services. Interactive Program Guide (IPG) data for television is delivered to integrated receiver-decoders (IRDs) in a decoder population via, for example, a satellite network. The IPG data provides scheduling information for global and local programming services which are carried via the satellite network as well as another network such as a CATV network or a terrestrial broadcast network. Each IRD is assigned to an IPG region using unit addressing. At the IRD, IPG data is filtered so that only the global data and the region-specific data for the IRD's IPG region is retained and processed by the IRD. Channel map data is also delivered to the IRDs so that bundles of IRD data can be filtered out using firmware filtering to discard program sources that are not present in the channel map. The IRD data which is retained after filtering is used to provide scheduling information via an on-screen display. A preferred source may be designated when there are duplicative channels on the different networks.

B. Claims 1, 9, 17, 25, 33, 41 and 49 are Patentable Under 35 U.S.C. § 102(b) over Eyer  
With Respect to Claim 1: Claim 1 recites:

*In a broadcasting system having a first service network broadcasting a first signal having a first set of program material and first program guide information describing at least a portion of said first set of program material, and a second service network broadcasting a second signal having a second set of program material and second program guide information describing at least a portion of said second set of program material, wherein the first broadcast signal and the second broadcast signal each include service channels uniquely described by a service channel identifier, a method of providing at least a portion of the second program guide information to a receiving station receiving the first signal, comprising the steps of:*  
*mapping at least a portion of the first program guide information to a first service channel of the first broadcast signal;*  
*mapping at least a portion of the second program guide information to a second service channel of the first broadcast signal, wherein the second service channel is logically offset from the first service channel; and*  
*transmitting the first signal to the receiving station;*  
*wherein the second program guide information includes data identifying the service network*  
*transmitting the second program guide information and wherein the first program guide information and the second program guide information is merged according to a comparison between the data and a receiver station configuration value.*



### 1. The First Office Action and the Applicant's Response

In rejecting claim 1, the first Office Action argued that Eyer discloses claim one's “*service network transmitting the second program guide information*” as follows:

...where the Local-IPG data includes station names or IDs, such as, ABC, NBC, CBS, CNN, Disney channel, etc., (fig. 2, col. 5, lines 60-67, col. 7, lines 36-45, and col. 9, lines 35-39) “data identifying the service network” transmitting the Local-IPG data and the Global-IPG data and the Local-IPG data is merged according to a comparison between the data and the IRD configuration value such as an address, identification number, geographical location, etc. associated with the IRD (col. 8, lines 57-67 and col. 10, lines 10-38). (recited on page 5, first full paragraph of the Final Office Action)

The Applicants pointed out that the station names or IDs referred to (ABC, NBC, CBS, etc.) do not identify the *service network transmitting the second program guide information*. Instead, they are *source* identifiers that indicate origin of the source material.

We refer to the portions of the Eyer reference upon which the Examiner relies. First, FIG.

2:




FIG.2

FIG. 2 simply refers to a “SOURCE ID” “SOURCE NAME.” The “SOURCE IDENTIFIER”, however, does not *identify the service network transmitting the second program guide information* as claim 1 recites, but rather, identifies the source of the underlying program material. This is made clear in the Eyer reference as follows:

In a second type of filtering, at each decoder, the IPG data may be filtered according to channel map data to enable each decoder to recover IPG data corresponding to channels accessible to that decoder while ignoring IPG data corresponding to channels not accessible to that decoder. Channel map data provides a correspondence between the programming services and a channel identifier which is displayed to the user, such as a channel number, **"source identifier" which identifies the programming service provider and/or station identifier (e.g., ABC, NBC)**. The channel map data may be in the form of a lookup table which associates carrier frequencies of the programming services with the corresponding identifier. For digital services, the channel map also indicates which programming service within the digital multiplex is to be associated with that channel. For example, an IRD may filter IPG data for a global programming service which is not transmitted or otherwise not available to the IRD, for example, due to operator preference or limited channel capacity in the cable network. (col. 4, lines 38-56, emphasis added)

The first Office Action also argued that the following discloses features of claim 1:

The IPG data provides program title, program description, and scheduling information for global (e.g., non-region-specific) programming, such as network programs (e.g., ABC, NBC, CBS, FOX) and other global satellite offerings (e.g., The Disney Channel, Nickelodeon, etc.) as well as scheduling information for region-specific programming, such as local news programs by independent stations or local network affiliates, and local access programs. (col. 5, lines 60-67)

The Applicants respectfully disagreed because the foregoing passage does not teach second program guide information identifying the service network transmitting the second program guide information.

The first Office Action further argued that the following discloses features of claim one:

For example, a "preferred source" data bit which is delivered to the IRDs can indicate which cable channels are preferred sources with a "1", while non-preferred cable channels are designated with a "0". Thus, if the duplicative channel "CNN" is received via both the satellite network and the CATV network, and the CATV channel is designated as a preferred source, the CATV channel will be displayed when selected by the user in lieu of the satellite channel. The "CNN" service carried on satellite will not be accessible by the user, even though it is available to the IRD's tuner/demodulator. (col. 7, lines 36-45)

The Applicants again respectfully disagreed. The foregoing describes how the Eyer system handles duplication of channels ... it does not disclose second program guide information identifying the service network transmitting the second program guide information.

Finally, the first Office Action relies on the following passage:

Specifically, the channel map provides a table which correlates three items, namely a user channel number (e.g., channel 10 for ABC), a physical location the received data stream, such as a PID, and a source identifier which is associated with each programming service. (col. 9, lines 35-39)

Again, the “source identifier” indicates the source of the underlying program material, not the service network transmitting second program guide information, as mandated by claim one.

The first Office Action also argued that the feature of merging the first program guide information and the second program guide information according to a comparison between the data and the receiver station value is disclosed as follows:

“Global-IPG data and the Local-IPG data is merged according to a comparison between the data and IRD 130 configuration value such as an address, identification number, geographical location, etc., associated with IRD 130.”

and relying on the following portions of the Eyer reference:

Thus, the IPG data which is received by the microprocessor 170 provides scheduling information for the global programming services, and for region-specific programming services for the IPG region of the particular IRD. In accordance with the present invention, regional IPG data is multicast addressed to IRDs in different IPG regions to allow each IRD to recover only the IPG data for its region. This reduces the amount of IPG data that must be processed by microprocessor 170, thereby reducing memory and CPU requirements, while still providing the user with IPG information for all programming available to the user's IRD. (col. 8, lines 57-67)

FIG. 4 illustrates the transmission and reception of global and regional IPG data in accordance with the present invention. IPG data bundles which are broadcast, e.g., over a satellite network to a user's home, include global IPG data in a bundle 0, or B0 (400), described below in greater detail, as well as IPG data for a specific IPG region, e.g., region A, in an associated bundle 1 or B1 (405), IPG data for a region B in an associated bundle B1 (410), and IPG data for a region C in an associated bundle B1 (415). Regions A, B and C are different IPG regions which are served by a common satellite broadcast network.

Each IRD receives the same global and region-specific IPG data bundles. However, in accordance with the present invention, IRD data bundles are filtered out in hardware based on multicast addresses so a specific IRD only needs to store and process IPG data for its region, along with the global IPG data. For example, the received bundles after filtering for an IRD in region A include only B0 (400) and B1 (405), the received bundles after filtering for an IRD in region B include only B0 (400) and B1 (410), and the received bundles after filtering for an IRD in region C include only B0 (400) and B1 (415).

Bundles allow an IRD to distinguish between two different IPG data blocks that are the same type of data (titles/schedules, for example) for the same time slot. Without the bundle numbers, the IRD can not distinguish between two data blocks of the same type and time slot, and would want to discard one as a duplicate. (col. 10, lines 10-38)

It is important to note that the first Office Action argues that the “source name” or “source identifier” described above was the “data identifying the service network transmitting the second program guide information.” Assuming arguendo that this is true (and for the reasons described above, it is not), that would require that first program guide information and second program guide information is merged according to a comparison between the “source name” or “source identifier” and a receiver configuration value. Plainly, this is not true. For example, the Eyer reference indicates that the “source name” would be, for example “ABC”. It would make no sense whatsoever to merge a program guide from one source and another source according to “ABC”. The reason for this nonsensical result is that the “source identifier” described in Eyer is not analogous to the “program guide information identifying the service network transmitting the second program guide information”.

## *2. The Final Office Action and the Applicant's Response*

The Final Office Action disagreed with the foregoing arguments, stating:

“Eyer teaches receiving national or global EPG and regional or local EPG (figs 1, col.5 lines 44-67 and col. 8, lines 6-32). By definition, ABC, NBC, CBS are networks, and furthermore, ABC, NBC, and CBS identify the service network where the program(s) originate.”

The cited portions of the Eyer reference are reproduced below:

IPG data, including global data which describes programming broadcast by satellite and national CATV networks, and region-specific data which describes programming broadcast only by CATV networks found within an assigned IPG region, is provided in a satellite data stream for television decoders which receive both satellite and cable television (CATV) transmissions.

FIG. 1 illustrates the transmission and reception of data via satellite and CATV paths in accordance with the present invention. The illustration provides a high-level functional overview of the present invention. A satellite multiplexer (MUX), modulator and encoder 100 receives IPG data for both global and local programming services (e.g., sources). IPG data from hundreds or even thousands of sources may be included. Ideally, IPG data for every program which is available via satellite and CATV is provided.

The IPG data provides program title, program description, and scheduling information for global (e.g., non-region-specific) programming, such as network programs (e.g., ABC, NBC, CBS, FOX) and other global satellite offerings (e.g., The Disney Channel, Nickelodeon, etc.) as well as scheduling information for region-specific programming, such as local news programs by independent stations or local network affiliates, and local access programs. (col. 5, lines 44-67)

The IPG translator 220 also receives configuration data, which includes associated parameters such as time slot size, output bit rate, look-ahead time, high-level data link controller (HDLC) address, group channel map (including group ID and group name), source channel map (including source ID, source name, group affiliation, and national or global data indicator), and a region map (including region ID, region name, and list of source IDs). A source ID is a number uniquely assigned to each program source in the system, and is used as an identifying reference in the IPG database.

The IPGT provides a continuous flow of IPG data at typically 20-200 kbps to a plurality of encoders, such as MPEG-2 encoders 1, . . . , N (220, . . . , 230). While MPEG-2 encoders are shown, other digital transport standards may be used. The encoders 220, . . . , 230 encode audio and video data from global and local programming services.

The encoders 220, . . . , 230 also receive Entitlement Management Message (EMM) data from a Subscriber Authorization Center (SAC) 240. This data, which is appended to the various programming services, authorizes the decoders to receive particular programming services, for example, according to a tiered marketing scheme. The encoders 220 and 230 output the programming services, IPG data, and EMM data to a MUX and modulation function 250 to provide a signal which is suitable for transmission by the transmitter 110. (col. 8, lines 6-32)

The Applicants respond:

The Applicants agree that ABC, NBC, and CBS are “networks”. However, they are not “service networks” within the meaning of claim one.

The preamble of claim 1 states that the first service network transmits a first signal having a first set of program material and first program guide information describing at least a portion of the first set of program material, and that the first broadcast signal has service channels uniquely identified by a service channel identifier. Let’s assume that the first service network is ABC.

Claim 1 also recites that the second service network transmits a second signal having a second set of program material and second program guide information describing at least a portion of the second program material, and that the second broadcast signal has service channels uniquely identified by a service channel identifier. Let’s assume that the second service network is NBC.

The body of claim 1 then recites that at least a portion of the first program guide information (ABC’s) is mapped to a first service channel of the first broadcast signal that is broadcast (by ABC) to the receiving station.

Nothing in Eyer suggests that ABC broadcasts a program guide on one of its service channels (presumably, one of the 2-13 channels of a television set). Even if it did, the body of the claim also recites that at least a portion of the second program guide information (NBC’s) is mapped to a second service channel (another of the 2-13 channels) of the first broadcast signal (broadcast by

ABC) wherein the second service channel is logically offset from the first service channel. This would mean that ABC is broadcasting, on one of its channels, program guide information for NBC's programs. Clearly, this is not the case. The reason the foregoing description doesn't work is simple ... it is because ABC, NBC, and CBS are not analogous to service networks.

The Final Office Action also argues:

“Furthermore, in situation where the service network, such as ABC is within the global and regional EPGs, Eyer uses duplicates to eliminate one from the other. Hence, applicant's arguments do not over the prior art of record Eyer, as Eyer's reference still meets the independent claims, is proper and maintained as discussed below”

The Applicants are unsure as to the meaning of this argument. It appears as if the Examiner is arguing that the two program guides are merged, but this does not address all of the features of the last clause of claim 1. Accordingly, the Applicants traverse.

Claims 9, 17, 25, 33, 41, and 49 recite features analogous to those of claim 1 and are patentable for the same reasons.

With Respect to Claims 2, 10, 18, 26, 33, and 42: Claims 2, 10, 18, 26, 33, and 42 recite that the second service channel is logically offset by an amount specified in the first program guide information. The Final Office Action argues that this is disclosed as follows:

An IPG translator (IPGT) configuration parameter, Source\_Channel\_Map, defines and describes program sources included in the downloaded IPG database. To differentiate between national and local sources, a flag “National” is used with following syntax.

```

45 Source_Channel_Map - LISTON /* One set of entries per source */
   <Source ID>, /* <Integer> <65536 */
   <Source Name>, /* <X-String>e.g. KPBS, A&E */
   <Group Name>, /* <X-String>e.g. PBS */
   <National>, /* <Boolean>*/
   <Display Group>, /* <Boolean>*/
50 <Premium>, /* <Boolean>*/
   <Priority>, /* <Boolean>*/
   ; /* Marks end of list */

```

When “National” is true, the source is considered a national source for IPG purposes. Otherwise, the source is local.

Respectfully, the Applicants do not see how the foregoing discloses a second service channel logically offset by an amount specified in the first program guide information ... especially when to be consistent with the rejection of claim 1, the service channels would have to be channels transmitted by service network (e.g. ABC, NBC, and CBS).


With Respect to Claims 3-7, 11-15, 19-23, 27-31, 35-39, and 43-47: Dependent claims 3-7, 11-15, 19-23, 27-31, 35-39, and 43-47 incorporate the limitations of their related independent claims, and are therefore patentable on this basis. In addition, these claims recite novel elements even more remote from the cited references. Accordingly, the Applicants respectfully request that these claims be allowed as well.

#### VIII. CONCLUSION

In light of the above arguments, Appellants respectfully submit that the cited references do not anticipate nor render obvious the claimed invention. More specifically, Appellants' claims recite novel physical features which patentably distinguish over any and all references under 35 U.S.C. §§ 102 and 103. As a result, a decision by the Board of Patent Appeals and Interferences reversing the Examiner and directing allowance of the pending claims in the subject application is respectfully solicited.

Respectfully submitted,

Date: March 22, 2006



Georgann S. Grunebach, Registration No.: 33,179  
Attorney for Appellants

The DIRECTV Group, Inc.  
RE/R08/A109  
2230 E. Imperial Highway  
P. O. Box 956  
El Segundo CA 90245-0956

Telephone No. (310) 964-4615

## CLAIMS APPENDIX

1. (PREVIOUSLY PRESENTED) In a broadcasting system having a first service network broadcasting a first signal having a first set of program material and first program guide information describing at least a portion of said first set of program material, and a second service network broadcasting a second signal having a second set of program material and second program guide information describing at least a portion of said second set of program material, wherein the first broadcast signal and the second broadcast signal each include service channels uniquely described by a service channel identifier, a method of providing at least a portion of the second program guide information to a receiving station receiving the first signal, comprising the steps of:

- mapping at least a portion of the first program guide information to a first service channel of the first broadcast signal;
- mapping at least a portion of the second program guide information to a second service channel of the first broadcast signal, wherein the second service channel is logically offset from the first service channel; and
- transmitting the first signal to the receiving station;

wherein the second program guide information includes data identifying the service network transmitting the second program guide information and wherein the first program guide information and the second program guide information is merged according to a comparison between the data and a receiver station configuration value.

2. (ORIGINAL) The method of Claim 1, wherein the second service channel is logically offset by an amount specified in the first program guide information.



3. (ORIGINAL) The method of Claim 1, wherein the portion of the second program guide information is transmitted at a different rate than the first program guide information.

4. (ORIGINAL) The method of Claim 1, wherein the first program guide information describes program material to be broadcast during a first time period, and the second program guide information describes program material to be broadcast during a second time period.

5. (ORIGINAL) The method of Claim 4, wherein the second time period is of different length than the first time period.

6. (ORIGINAL) The method of Claim 1, further comprising the steps of:  
receiving the first signal; and  
storing the first program guide information and the second program guide information for subsequent retrieval.

7. (ORIGINAL) The method of Claim 6, further comprising the steps of:  
merging the first program guide information and the second program guide information to produce a merged program guide; and  
retrieving the merged program guide in response to a subscriber request.

8. (CANCELED)

9. (PREVIOUSLY PRESENTED) In a broadcasting system having a first service network broadcasting a first signal having a first set of program material and first program guide information describing at least a portion of said first set of program material, and a second service network broadcasting a second signal having a second set of program material and second program guide information describing at least a portion of said second set of program material, wherein the first broadcast signal and the second broadcast signal each include service channels uniquely described by a service channel identifier, a method of obtaining at least a portion of the second program guide information via the first signal, comprising the steps of:

receiving the first signal, wherein the first signal includes:

a first service channel having at least a portion of the first program guide information;

a second service channel having at least a portion of the second program guide information;

wherein the second service channel is logically offset from the first service channel;

and

presenting the first program guide information and the second program guide information to a subscriber;

wherein the second program guide information includes data identifying the service network transmitting the second program guide information and wherein the first program guide information and the second program guide information is merged according to a comparison between the data and a receiver station configuration value.

10. (ORIGINAL) The method of Claim 9, wherein the second service channel is logically offset by an amount specified in the first program guide information.

11. (ORIGINAL) The method of Claim 9, wherein the portion of the second program guide information is received at a different rate than the first program guide information.

12. (ORIGINAL) The method of Claim 9, wherein the first program guide information describes program material to be broadcast during a first time period, and the second program guide information describes program material to be broadcast during a second time period.

13. (ORIGINAL) The method of Claim 12, wherein the second time period is of different length than the first time period.

14. (ORIGINAL) The method of Claim 9, further comprising the steps of:  
storing the first program guide information and the second program guide information for subsequent retrieval.

15. (ORIGINAL) The method of Claim 14, further comprising the steps of:

merging the first program guide information and the second program guide information to produce a merged program guide; and

retrieving the merged program guide in response to a subscriber request.

16. (CANCELED)

17. (PREVIOUSLY PRESENTED) In a broadcasting system having a first service network broadcasting a first signal having a first set of program material and first program guide information describing at least a portion of said first set of program material, and a second service network broadcasting a second signal having a second set of program material and second program guide information describing at least a portion of said second set of program material, wherein the first broadcast signal and the second broadcast signal each include service channels uniquely described by a service channel identifier, an apparatus of providing at least a portion of the second program guide information to a receiver station receiving the first signal, comprising:

a program guide subsystem for mapping at least a portion of the first program guide information to a first service channel of the first broadcast signal, and mapping at least a portion of the second program guide information to a second service channel of the first broadcast signal, wherein the second service channel is logically offset from the first service channel; and

a transmitter for transmitting the first signal to the receiver station;

wherein the second program guide information includes data identifying the service network transmitting the second program guide information and wherein the first program guide information and the second program guide information is merged according to a comparison between the data and a receiver station configuration value.

18. (ORIGINAL) The apparatus of Claim 17, wherein the second service channel is logically offset by an amount specified in the first program guide information.

19. (ORIGINAL) The apparatus of Claim 17, wherein the portion of the second program guide information is transmitted at a different rate than the first program guide information.

20. (ORIGINAL) The apparatus of Claim 17, wherein the first program guide information describes program material to be broadcast during a first time period, and the second program guide information describes program material to be broadcast during a second time period.

21. (ORIGINAL) The apparatus of Claim 20, wherein the second time period is of different length than the first time period.

22. (ORIGINAL) The apparatus of Claim 17, further comprising:  
a tuner for receiving the first signal; and  
a memory for storing the first program guide information and the second program guide information for subsequent retrieval.

23. (ORIGINAL) The apparatus of Claim 22, wherein the program guide subsystem further comprises:

a module for merging the first program guide information and the second program guide information to produce a merged program guide, and for retrieving the merged program guide in response to a subscriber request.

24. (CANCELED)

25. (PREVIOUSLY PRESENTED) In a broadcasting system having a first service network broadcasting a first signal having a first set of program material and first program guide information describing at least a portion of said first set of program material, and a second service network broadcasting a second signal having a second set of program material and second program guide information describing at least a portion of said second set of program material, wherein the first broadcast signal and the second broadcast signal each include service channels uniquely described by a service channel identifier, an apparatus for obtaining at least a portion of the second program guide information via the first signal, comprising the steps:

a tuner for receiving the first signal, wherein the first signal includes:

a first service channel having at least a portion of the first program guide information;

a second service channel having at least a portion of the second program guide information;

wherein the second service channel is logically offset from the first service channel;

and

a presentation device for providing the first program guide information and the second program guide information to a subscriber;

wherein the second program guide information includes data identifying the service network transmitting the second program guide information and wherein the first program guide information and the second program guide information is merged according to a comparison between the data and a receiver station configuration value.



26. (ORIGINAL) The apparatus of Claim 25, wherein the second service channel is logically offset by an amount specified in the first program guide information.

27. (ORIGINAL) The apparatus of Claim 25, wherein the portion of the second program guide information is received at a different rate than the first program guide information.

28. (ORIGINAL) The apparatus of Claim 25, wherein the first program guide information describes program material to be broadcast during a first time period, and the second program guide information describes program material to be broadcast during a second time period.

29. (ORIGINAL) The apparatus of Claim 28, wherein the second time period is of different length than the first time period.

30. (ORIGINAL) The apparatus of Claim 25, further comprising:  
a memory for storing the first program guide information and the second program guide information for subsequent retrieval.

31. (ORIGINAL) The apparatus of Claim 30, further comprising:  
a module for merging the first program guide information and the second program guide information to produce a merged program guide and for retrieving the merged program guide in response to a subscriber request.

32. (CANCELED)

33. (PREVIOUSLY PRESENTED) In a broadcasting system having a first service network broadcasting a first signal having a first set of program material and first program guide information describing at least a portion of said first set of program material, and a second service network broadcasting a second signal having a second set of program material and second program guide information describing at least a portion of said second set of program material, wherein the first broadcast signal and the second broadcast signal each include service channels uniquely described by a service channel identifier, an apparatus for providing at least a portion of the second program guide information to a receiver station receiving the first signal, comprising:

means for mapping at least a portion of the first program guide information to a first service channel of the first broadcast signal;

means for mapping at least a portion of the second program guide information to a second service channel of the first broadcast signal, wherein the second service channel is logically offset from the first service channel; and

means for transmitting the first signal to the receiver station;

wherein the second program guide information includes data identifying the service network transmitting the second program guide information and wherein the first program guide information and the second program guide information is merged according to a comparison between the data and a receiver station configuration value.

34. (ORIGINAL) The apparatus of Claim 33, wherein the second service channel is logically offset by an amount specified in the first program guide information.

35. (ORIGINAL) The apparatus of Claim 33, wherein the portion of the second program guide information is transmitted at a different rate than the first program guide information.

36. (ORIGINAL) The apparatus of Claim 33, wherein the first program guide information describes program material to be broadcast during a first time period, and the second program guide information describes program material to be broadcast during a second time period.

37. (ORIGINAL) The apparatus of Claim 36, wherein the second time period is of different length than the first time period.

38. (ORIGINAL) The apparatus of Claim 33, further comprising:  
means for receiving the first signal; and  
means for storing the first program guide information and the second program guide information for subsequent retrieval.

39. (ORIGINAL) The apparatus of Claim 38, further comprising:  
means for merging the first program guide information and the second program guide information to produce a merged program guide; and  
means for retrieving the merged program guide in response to a subscriber request.

40. (CANCELED)

41. (PREVIOUSLY PRESENTED) In a broadcasting system having a first service network broadcasting a first signal having a first set of program material and first program guide information describing at least a portion of said first set of program material, and a second service network broadcasting a second signal having a second set of program material and second program guide information describing at least a portion of said second set of program material, wherein the first broadcast signal and the second broadcast signal each include service channels uniquely described by a service channel identifier, an apparatus for obtaining at least a portion of the second program guide information via the first signal, comprising:

means for receiving the first signal, wherein the first signal includes:

a first service channel having at least a portion of the first program guide information;

a second service channel having at least a portion of the second program guide information;

wherein the second service channel is logically offset from the first service channel;

and

means for presenting the first program guide information and the second program guide information to a subscriber;

wherein the second program guide information includes data identifying the service network transmitting the second program guide information and wherein the first program guide information and the second program guide information is merged according to a comparison between the data and a receiver station configuration value.

42. (ORIGINAL) The apparatus of Claim 41, wherein the second service channel is logically offset by an amount specified in the first program guide information.

43. (ORIGINAL) The apparatus of Claim 41, wherein the portion of the second program guide information is received at a different rate than the first program guide information.

44. (ORIGINAL) The apparatus of Claim 41, wherein the first program guide information describes program material to be broadcast during a first time period, and the second program guide information describes program material to be broadcast during a second time period.

45. (ORIGINAL) The apparatus of Claim 44, wherein the second time period is of different length than the first time period.

46. (ORIGINAL) The apparatus of Claim 41, further comprising:  
means for storing the first program guide information and the second program guide information for subsequent retrieval.

47. (ORIGINAL) The apparatus of Claim 46, further comprising:  
means for merging the first program guide information and the second program guide information to produce a merged program guide; and  
means for retrieving the merged program guide in response to a subscriber request.

48. (CANCELED)

49. (PREVIOUSLY PRESENTED) In a broadcasting system having a first service network broadcasting a first signal having a first set of program material and first program guide information describing at least a portion of said first set of program material, and a second service network broadcasting a second signal having a second set of program material and second program guide information describing at least a portion of said second set of program material, wherein the first broadcast signal and the second broadcast signal each include service channels uniquely described by a service channel identifier, a signal embodied in a carrier wave, the signal produced by performing the method steps of:

mapping at least a portion of the first program guide information to a first service channel of the first broadcast signal;

mapping at least a portion of the second program guide information to a second service channel of the first broadcast signal, wherein the second service channel is logically offset from the first service channel; and

transmitting the first signal;

wherein the second program guide information includes data identifying the service network transmitting the second program guide information and wherein the first program guide information and the second program guide information is merged according to a comparison between the data and a receiver station configuration value.

## **EVIDENCE APPENDIX**

(none)



**RELATED APPEALS AND INTERFERENCES APPENDIX**

(none)